**Product**
**360 Masonry**

**Description**
360 Masonry for the trade contains added high performance resin to provide a durable long life decorate finish for external surfaces. Containing a minimum of 50% recycled content our re-engineered paint applies and covers like a traditional masonry.

**Recommended Uses**
Suitable for external walls, cement rendering, brick, stone, blockwork and pebble dash etc

**Colour Range**
Please refer to our product guide.
**Finish**
Matt
**Size**
5 Litres, 10 Litres

**Coverage**
Approximately 10m$^2$ per litre depending on the nature and porosity of the surface being painted. 2 coats are normally required.

**Drying Time**
Touch Dry in 1-2 hours.
Recoat after 4-6 hours.

**Transport & Storage**
To avoid risk of spillage, always store and transport in a secure upright position. Lift with care. Do not use empty container for storing food. Protect from frost.

**Thinner**
Clean water.

**Surface Preparation**
All surfaces should be clean, dry and free from loose flaking material. Repair cracks and defective areas and treat any existing mould and algae growth with a suitable surface biocide. Wear a suitable face mask if creating dust.

**Application Method**
Brush, roller, or spray.
Ensure good ventilation during application and drying. Do not breathe spray.
Stir well before use. If more than one can of colour is to be used in the same area intermix before use.
Do not apply below 8 degrees centigrade or when rain is imminent.

**Cleaning**
Remove as much product as possible from equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Dispose content and container in accordance with local, regional, national regulations. Do not empty waste into water courses, streams, ponds etc.

**Precautions**
- If medical advice is needed have container or label to hand.
- Keep out of reach from children.
- Do not breathe spray.
- Wear protective gloves.
- IF ON SKIN: wash with plenty of soap and water.
- If skin irritation or rash occurs get medical advice/attention.
- Wash contaminated clothing before re use.
- Avoid contact with eyes.
- Do not ingest.
- Please refer to product label & Safety Data Sheet (SDS).
- SDS available on request.

Version 1
November 2025

Paint 360 Ltd
Belfont Trading Estate, Mucklow Hill,
Halesowen, B62 8DR
Tel: 0121 561 5353
www.paint360.co.uk